

Revision date:  
16.02.2021**BIZOL Allround ATF DVI**

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BIZOL Allround ATF DVI

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant

**1.3. Details of the supplier of the safety data sheet**

Company name:	BIZOL BITA Trading GmbH		
Street:	Martin-Buber-Str. 12		
Place:	D-14163 Berlin		
Telephone:	+49 (30) 804 869-0	Telefax:	+49 (30) 804 869-2860
e-mail:	support@bizol.de		
Internet:	www.bizol.com		

**1.4. Emergency telephone number:**

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P273 Avoid release to the environment.

**2.3. Other hazards**

Results of PBT and vPvB assessment: not applicable.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mineral oil-based mixture. Mineral oil with DMSO extract &lt; 3 % as measured by IP 346.

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 2 of 9

### Hazardous components

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	GHS Classification	
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic	25 - <= 100 %
	265-157-1 649-467-00-8 01-2119484627-25	
	Asp. Tox. 1; H304	
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	10 - < 20 %
	276-738-4 649-483-00-5 01-2119474889-13	
	Asp. Tox. 1; H304	
72623-86-0	lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	1 - < 2.5 %
	276-737-9 649-482-00-X 01-2119474878-16	
	Asp. Tox. 1; H304	
36878-20-3	bis(nonylphenyl)amine	1 - < 2.5 %
	253-249-4 01-2119488911-28	
	Aquatic Chronic 4; H413	
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	1 - < 2.5 %
	406-040-9 607-530-00-7 01-0000015551-76	
	Aquatic Chronic 4; H413	
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	0.1 - < 0.3 %
	424-820-7 01-0000017126-75	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H312 H314 H318 H400 H410	

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	distillates (petroleum), hydrotreated heavy paraffinic	25 - <= 100 %
		dermal: LD50 = > 5000,0 mg/kg; oral: LD50 = > 5000,0 mg/kg	
72623-87-1	276-738-4	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	10 - < 20 %
		dermal: LD50 = > 2000,0 mg/kg; oral: LD50 = > 2000,0 mg/kg	
	424-820-7	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	0.1 - < 0.3 %
		dermal: ATE = 1100 mg/kg M akut; H400: M=10 M chron.; H410: M=10	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

Revision date:  
16.02.2021

**BIZOL Allround ATF DVI**

Page 3 of 9

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Protective measures: see section 7 + 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Protective measures: see section 7 + 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

No special measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 4 of 9

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic			
Consumer DNEL, long-term		inhalation	local	1,2 mg/m³
Worker DNEL, long-term		inhalation	local	5,4
36878-20-3	bis(nonylphenyl)amine			
Worker DNEL, long-term		dermal	systemic	0,62 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	4,37 mg/m³
Consumer DNEL, long-term		oral	systemic	0,31 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,31 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,09 mg/m³
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, acute		dermal	systemic	20 mg/kg bw/day
Worker DNEL, acute		dermal	local	1 mg/cm²
Worker DNEL, long-term		dermal	systemic	0,22 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,006 mg/cm²

### PNEC values

CAS No	Substance	Value
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic	
Secondary poisoning		9,33 mg/kg
36878-20-3	bis(nonylphenyl)amine	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		132000 mg/kg
Marine sediment		13200 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Freshwater		0,0043 mg/l
Marine water		0,0043 mg/l
Freshwater sediment		233 mg/kg
Marine sediment		23,3 mg/kg
Soil		189 mg/kg
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
Freshwater		0,036 mg/l
Freshwater sediment		0,128 mg/kg
Soil		0,104 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

See section 7. No additional measures necessary.

#### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 5 of 9

### Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Skin protection

Protective clothing.

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	red
Odour:	characteristic

#### Test method

pH-Value:	not applicable
-----------	----------------

#### Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	<= -39 °C ASTM D 7346
Flash point:	>= 200 °C EN ISO 2592
Lower explosion limits:	0,4 vol. %
Upper explosion limits:	4,5 vol. %
Auto-ignition temperature:	not determined
Decomposition temperature:	No information available.
Vapour pressure: (at 20 °C)	< 0,1 hPa
Density (at 15 °C):	0,85 g/cm³ DIN EN ISO 12185
Water solubility:	insoluble
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 40 °C)	34 mm²/s ASTM D 7042
Flow time:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined

### 9.2. Other information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 6 of 9

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4. Conditions to avoid

Heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 > 5000,0 mg/kg	Rat		
	dermal	LD50 > 5000,0 mg/kg	Rabbit		
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
	oral	LD50 > 2000,0 mg/kg	Rat		
	dermal	LD50 > 2000,0 mg/kg	Rabbit		
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol				
	dermal	ATE 1100 mg/kg			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself.

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol					
	Acute fish toxicity	LC50 1,5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	
	Acute algae toxicity	ErC50 0,31 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 0,09 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
	Crustacea toxicity	NOEC 0,14 mg/l	21 d	ECHA		

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based			
	Biodegradation	49,0 %		
36878-20-3	bis(nonylphenyl)amine			
	OECD 301B	1 %	28	ECHA
	Not readily biodegradable (according to OECD criteria)			

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	>4,00
36878-20-3	bis(nonylphenyl)amine	3,60

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.7. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

#### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## SECTION 14: Transport information

### Land transport (ADR/RID)

Revision date:  
16.02.2021

## BIZOL Allround ATF DVI

Page 8 of 9

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

Marine pollutant:

NO

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

#### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

### Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

WEL (UK): Workplace Exposure Limits



Revision date:  
16.02.2021**BIZOL Allround ATF DVI**

Page 9 of 9

TWA (EC): Time-Weighted Average

STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration

ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

-----  
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*