

according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 1 of 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Bizol Chain+ L53

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Lubricant

# 1.3. Details of the supplier of the safety data sheet

Company name: Street: Place:	BIZOL BITA Trading GmbH Martin-Buber-Str. 12 D-14163 Berlin	
Telephone: e-mail: Internet:	+49 (30) 804 869-0 support@bizol.de www.bizol.com	Telefax:+49 (30) 804 869-2860
<u>1.4. Emergency telephone</u> number:	Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr) In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166	

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories: Flammable gas: Flam. Gas 1 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

**Pictograms:** 



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H412	Harmful to aquatic life with long lasting effects.

# Precautionary statements

5
Keep out of reach of children.
Do not breathe aerosols.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of waste according to applicable legislation.

### 2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

### **SECTION 3: Composition/information on ingredients**



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 2 of 8

### 3.2. Mixtures

### **Chemical characterization**

Blend of the following materials with non-hazardous additives.

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according	to Regulation (EC) No. 1272/2008 [C	CLP]	
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compress	sed gas; H220 H280		
106-97-8	butane			5 - < 10 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compress	sed gas; H220 H280	,	
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compress	sed gas; H220 H280		
109-66-0	pentane			5 - < 10 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 1, STOT SE	3, Asp. Tox. 1, Aquatic Chronic 2; H22	24 H336 H304 H411 EUH066	

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

# Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 3 of 8

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

See protective measures under point 7 and 8.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

### Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

### Advice on protection against fire and explosion

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only non-sparking tools. Recommendation: Wear anti-static footwear and clothing

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

# 7.3. Specific end use(s)

Observe technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-66-0	Pentane	600	1800		TWA (8 h)	WEL
		-	_		STEL (15 min)	WEL

### 8.2. Exposure controls

# Appropriate engineering controls

See chapter 7. No additional measures necessary.

## Protective and hygiene measures

When using do not eat, drink, smoke, sniff.



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 4 of 8

### Eye/face protection

Eye glasses with side protection.

## Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

# Skin protection

Protective clothing.

## **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device (EN 14387), e.g. A P.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	light yellow	
Odour:	characteristic	
	T	Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	not applicable	
Pour point:	not applicable	
Flash point:	< 0 °C	
Explosive properties The product is: not explosive. In	use, may form flammable/explosive vapour-air mixture.	
Lower explosion limits:	1,7 vol. %	
Upper explosion limits:	10,9 vol. %	
Ignition temperature:	240 °C	
Decomposition temperature:	No information available.	
Vapour pressure: (at 20 °C)	8300 hPa	
Density:	0,72 g/cm³	
Water solubility:	Immiscible	
Partition coefficient:	not determined	
Viscosity / dynamic:	not determined	
Viscosity / kinematic:	not determined	
Flow time:	not determined	
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
No information available.		

### **SECTION 10: Stability and reactivity**



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 5 of 8

### 10.1. Reactivity

No information available.

# 10.2. Chemical stability

No information available.

# 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

# 10.4. Conditions to avoid

Heat.

# 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

No information available.

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

### Acute toxicity

Based on available data, the classification criteria are not met.

### **ATEmix calculated**

ATE (inhalative gas) 6646,5 ppm

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
106-97-8	butane	-		-	
	inhalative (4 h) gas	LC50	658 ppm	Rat	GESTIS
109-66-0	pentane	_			
	inhalative (4 h) vapour	LC50	364 mg/l	Rat	GESTIS

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

# Aspiration hazard

Based on available data, the classification criteria are not met.

### Practical experience

### Other observations

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

# **SECTION 12: Ecological information**

# 12.1. Toxicity

There are no data available on the mixture itself.

# 12.2. Persistence and degradability

There are no data available on the mixture itself.

# 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

Page 6 of 8

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89
75-28-5	isobutane	2,8
109-66-0	pentane	3,39

#### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

#### 12.6. Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## Advice on disposal

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### Waste disposal number of waste from residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); solvents Classified as hazardous waste.

# Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

# Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

UN 1950
AEROSOLS
2
-
2.1
5F
190 327 344 625
1 L
E0
2
D
UN 1950
AEROSOLS
2.1



according to Regulation (EC) No 1907/2006

	Bizol Chain+ L53	
Revision date: 12.07.2017		Page 7 of 8
14.4. Packing group:	-	
Hazard label:	2.1	
Marine pollutant:	NO	
Special Provisions: Limited quantity:	63, 190, 277, 327, 344, 959 1000 mL	
Excepted quantity:	EO	
EmS:	F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS, flammable	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203 E0	
Excepted quantity: IATA-packing instructions - Passenger:	203	
IATA-packing instructions - Lassenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user No data available		
14.7. Transport in bulk according to Annex No data available	II of Marpol and the IBC Code	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII)	:	
Entry 28: butane; isobutane		
2010/75/EU (VOC):	40 % (288 g/l)	
National regulatory information		
Water contaminating class (D):	1 - slightly water contaminating	
15.2. Chemical safety assessment		
Chemical safety assessments for subs	stances in this mixture were not carried out.	
SECTION 16: Other information		

# Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,7,8,9,11,13,14,15.

## Abbreviations and acronyms

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations



according to Regulation (EC) No 1907/2006

# **Bizol Chain+ L53**

Revision date: 12.07.2017

concerning the International Carriage of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association ICAO: International Civil Aviation Organization CAS: Chemical Abstracts Service (a division of the American Chemical Society) DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average STEL (EC): Short Term Exposure Limit ATE: Acute Toxicity Estimate LD50: Lethal Dose, 50% (median lethal dose) LC50: Lethal Concentration, 50% (median lethal concentration) EC50: half maximal Effective Concentration ErC50: EC50 in terms of reduction of growth rate VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

# Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

# **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Page 8 of 8