

Revision date:  
07.02.2020**BIZOL Technology 5W-20 ECO**

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BIZOL Technology 5W-20 ECO

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil

**1.3. Details of the supplier of the safety data sheet**

Company name:	BIZOL BITA Trading GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

**1.4. Emergency telephone number:**

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Special labelling of certain mixtures**

EUH208	Contains C14-16-18 alkylphenol, molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**2.3. Other hazards**

Results of PBT and vPvB assessment: not applicable.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mineral oil-based mixture. Mineral oil with DMSO extract &lt; 3 % as measured by IP 346.

Revision date:  
07.02.2020

## BIZOL Technology 5W-20 ECO

Page 2 of 9

### Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic	25 - <= 100 %
	265-157-1	
	649-467-00-8	
	01-2119484627-25	
	Asp. Tox. 1; H304	
36878-20-3	bis(nonylphenyl)amine	1 - < 2.5 %
	253-249-4	
	01-2119488911-28	
	Aquatic Chronic 4; H413	
1190625-94-5	C14-16-18 alkylphenol	1 - < 2.5 %
	931-468-2	
	01-2119498288-19	
	Skin Sens. 1B, STOT RE 2; H317 H373	

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	distillates (petroleum), hydrotreated heavy paraffinic	25 - <= 100 %
		dermal: LD50 = > 5000,0 mg/kg; oral: LD50 = > 5000,0 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

Revision date:  
07.02.2020

**BIZOL Technology 5W-20 ECO**

Page 3 of 9

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Protective measures: see section 7 + 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Protective measures: see section 7 + 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

No special measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Revision date:  
07.02.2020

## BIZOL Technology 5W-20 ECO

Page 4 of 9

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
DNEL type				
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic			
Consumer DNEL, long-term		inhalation	local	1,2 mg/m³
Worker DNEL, long-term		inhalation	local	5,4
36878-20-3	bis(nonylphenyl)amine			
Worker DNEL, long-term		dermal	systemic	0,62 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	4,37 mg/m³
Consumer DNEL, long-term		oral	systemic	0,31 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,31 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,09 mg/m³
1190625-94-5	C14-16-18 alkylphenol			
Worker DNEL, long-term		inhalation	systemic	1,17 mg/m³
Worker DNEL, long-term		dermal	systemic	0,3 mg/kg bw/day

### PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic	
Secondary poisoning		9,33 mg/kg
36878-20-3	bis(nonylphenyl)amine	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		132000 mg/kg
Marine sediment		13200 mg/kg
1190625-94-5	C14-16-18 alkylphenol	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		4266 mg/kg
Marine sediment		422,6 mg/kg
Soil		852,58 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

See section 7. No additional measures necessary.

#### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

#### Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber).

Breakthrough time:: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Revision date:  
07.02.2020

**BIZOL Technology 5W-20 ECO**

Page 5 of 9

**Skin protection**

Protective clothing.

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	light brown	
Odour:	characteristic	
		<b>Test method</b>
pH-Value:	not applicable	
<b>Changes in the physical state</b>		
Melting point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Pour point:	<= -39 °C	ASTM D 7346
Flash point:	>= 210 °C	EN ISO 2592
Lower explosion limits:	0,9 vol. %	
Upper explosion limits:	7,0 vol. %	
Auto-ignition temperature:	not determined	
Decomposition temperature:	No information available.	
Vapour pressure: (at 20 °C)	< 0,1 hPa	
Density (at 15 °C):	0,85 g/cm³	DIN EN ISO 12185
Water solubility:	insoluble	
Partition coefficient n-octanol/water:	not determined	
Viscosity / dynamic:	not determined	
Viscosity / kinematic: (at 40 °C)	47 mm²/s	ASTM D 7042
Flow time:	not determined	
Relative vapour density:	not determined	
Evaporation rate:	not determined	

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

Revision date:  
07.02.2020

## BIZOL Technology 5W-20 ECO

Page 6 of 9

### 10.4. Conditions to avoid

Heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 > 5000,0 mg/kg	Rat		
	dermal	LD50 > 5000,0 mg/kg	Rabbit		

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Contains C14-16-18 alkylphenol, molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself.

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
36878-20-3	bis(nonylphenyl)amine			
	OECD 301B	1 %	28	ECHA
	Not readily biodegradable (according to OECD criteria)			

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Revision date:  
07.02.2020

## BIZOL Technology 5W-20 ECO

Page 7 of 9

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
36878-20-3	bis(nonylphenyl)amine	3,60

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.7. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

#### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.
Marine pollutant:	NO

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

Revision date:  
07.02.2020**BIZOL Technology 5W-20 ECO**

Page 8 of 9

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 0 %  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,9,15.

**Abbreviations and acronyms**

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
CAS: Chemical Abstracts Service (a division of the American Chemical Society)  
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
STEL (EC): Short Term Exposure Limit  
ATE: Acute Toxicity Estimate  
LD50: Lethal Dose, 50% (median lethal dose)  
LC50: Lethal Concentration, 50% (median lethal concentration)  
EC50: half maximal Effective Concentration  
ErC50: EC50 in terms of reduction of growth rate  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs (liver) through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains C14-16-18 alkylphenol, molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

-----  
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Revision date:  
07.02.2020

**BIZOL Technology 5W-20 ECO**

Page 9 of 9

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*